

Monrovia Press

2022-2026 Subaru WRX (VB) No-Drill Front License Plate Mount
<https://monroviapress.com> | info@monroviapress.com

Hardware Included

- Back Mount
- Front Mount
- License plate frame
- 4x #10-24 x 1" screws
- 4x #10-24 1/4" screws
- 2x #10 x 3/4" screws

Tools Required

- #2 Phillips screwdriver
- Masking tape (optional)

Installation Steps

1. Orient the back mount with the arrow facing towards you and pointing upward. Slide it through the lower grill opening and hold it centered in the top hole, sitting flush against the back of the grill.
2. Press the front mount against the back mount. If needed, use a strip of masking tape to temporarily hold the two pieces together. The
3. Using the four 1" screws, fasten the front and back mounts together through their aligned holes. Tighten with your screwdriver until snug.
4. Place the rubber bumpers on the back top corners of the license plate frame to prevent possible scratches.
5. Hold the license plate frame up to the installed mount base, aligning it with the two pre-formed pilot holes. Drive the 2 self-tapping screws through the pilot holes to secure the frame. Avoid over-tightening to prevent stripping the holes.
6. Attach your license plate to the frame using the 4 remaining 1/4" screws. Tighten until secure.

Installation complete. No drilling required, all fasteners are mechanical and reversible. If the mount feels loose after installation, recheck that both mounts are flush, and all 4 joining screws are fully tightened.

Scan here for the instructions with reference images.

